

■ Simplified outline(SOT-323)


■ Marking

| | |
|---------|----|
| Marking | KN |
|---------|----|

■ MOSFET MAXIMUM RATINGS ($T_a = 25^\circ\text{C}$ unless otherwise noted)






| Symbol | Parameter | Value | Units |
|-----------------|---|----------|-----------------------------|
| V_{DS} | Drain-Source voltage | 30 | V |
| V_{GSS} | Gate-Source Voltage | ± 20 | V |
| I_D | Continuous Drain Current | 0.1 | A |
| P_D | Power Dissipation | 0.2 | W |
| T_J | Junction Temperature | 150 | $^\circ\text{C}$ |
| T_{STG} | Storage Temperature | -55-150 | $^\circ\text{C}$ |
| $R_{\theta JA}$ | Thermal Resistance from Junction to Ambient | 625 | $^\circ\text{C} / \text{W}$ |

Equivalent circuit



■ MOSFET ELECTRICAL CHARACTERISTICS($T_a=25^\circ\text{C}$ unless otherwise noted)

| Parameter | Symbol | Test Condition | Min | Typ | Max | Units |
|-----------------------------------|---------------------|--|-----|-----|-----------|---------------|
| Off Characteristics | | | | | | |
| Drain-Source Breakdown Voltage | $V_{(BR)DSS}$ | $V_{GS} = 0V, I_D = 10\mu\text{A}$ | 30 | | | V |
| Zero Gate Voltage Drain Current | I_{DSS} | $V_{DS} = 30V, V_{GS} = 0V$ | | | 0.2 | μA |
| Gate –Source leakage current | I_{GS} | $V_{GS} = \pm 20V, V_{DS} = 0V$ | | | ± 500 | nA |
| Gate Threshold Voltage | $V_{GS(\text{th})}$ | $V_{DS} = 3V, I_D = 100\mu\text{A}$ | 0.8 | | 1.5 | V |
| Drain-Source On-Resistance | $R_{DS(on)}$ | $V_{GS} = 4V, I_D = 10\text{mA}$ | | | 8 | Ω |
| | | $V_{GS} = 2.5V, I_D = 1\text{mA}$ | | | 13 | Ω |
| Forward Transconductance | g_{FS} | $V_{DS} = 3V, I_D = 10\text{mA}$ | 20 | | | mS |
| Dynamic Characteristics* | | | | | | |
| Input Capacitance | C_{iss} | $V_{DS} = 5V, V_{GS} = 0V, f = 1\text{MHz}$ | | 13 | | pF |
| Output Capacitance | C_{oss} | | | 9 | | pF |
| Reverse Transfer Capacitance | C_{rss} | | | 4 | | pF |
| Switching Characteristics* | | | | | | |
| Turn-On Delay Time | $t_{d(on)}$ | $V_{GS} = 5V, V_{DD} = 5V, I_D = 10\text{mA}, R_g = 10\Omega, R_L = 500\Omega$ | | 15 | | ns |
| Rise Time | t_r | | | 35 | | ns |
| Turn-Off Delay Time | $t_{d(off)}$ | | | 80 | | ns |
| Fall Time | t_f | | | 80 | | ns |

*These parameters have no way to verify.

Output Characteristics

Transfer Characteristics

R_{DS(ON)} — I_D

R_{DS(ON)} — V_{GS}

I_S — V_{SD}


■ SOT-323


DIMENSIONS (mm are the original dimensions)

| UNIT | A | A_1 max | b_p | c | D | E | e | e_1 | H_E | L_p | Q | v | w |
|------|------------|--------------|------------|--------------|------------|--------------|-----|-------|------------|--------------|--------------|-----|-----|
| mm | 1.1 0.8 | 0.1 | 0.4 0.3 | 0.25 0.10 | 2.2 1.8 | 1.35 1.15 | 1.3 | 0.65 | 2.2 2.0 | 0.45 0.15 | 0.23 0.13 | 0.2 | 0.2 |